

**Amendments to the Claims:**

A clean version of the entire set of pending claims, including amendments to the claims, is submitted herewith per 37 CFR 1.121(c)(3). This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Currently Amended) A color projection system comprising:  
a light valve device (4)-for modulating light incident thereon in accordance with information of an image to be displayed;  
an AC-operated light source (1)-for generating light of at least two different colors, and  
an illumination unit (3)-for illuminating said light valve device with said generated light of different colors in a sequential fashion;  
wherein said light valve device (4)-is controlled in synchronization with said illumination unit in order to produce a colored output image;  
~~characterized in that~~wherein the sequential color cycle of the light valve device (4)-and the AC cycle for the illumination unit (3)-are adapted to be out of phase with each other.
2. (Currently Amended) The projection system as claimed in claim 1, wherein the light valve device (4)-is a transmissive or a reflective liquid crystal device.
3. (Currently Amended) The projection system as claimed in claim 1, wherein the illumination unit (3)-is further adapted to generate different colors in a space-multiplexed fashion.
4. (Currently Amended) The projection system as claimed in claim 3, wherein the illumination unit (3)-is operable to produce a continuous spatial color split,

whereby at any certain moment of time all colors are projected on the light valve device.

5. (Currently Amended) The projection system as claimed in claim 3, wherein the illumination unit (3)-is operable to provide scrolling color projection, wherein the colors are arranged with band-shaped cross-section.

6. (Currently Amended) The projection system as claimed in claim 1, wherein the illumination unit (3)-comprises a source of white light, and a beam splitter for splitting said white light into a first, a second and a third color beam.

7. (Currently Amended) A method of controlling a projection system with an AC-operated light source (1)-for generating light of at least two different colors, said light of different colors being illuminated on a light valve device (4)-in a sequential fashion, the light valve being controlled to modulate the light incident thereon in accordance with information of an image to be displayed, and in synchronization with said color sequential illumination unit-(3), in order to produce a colored output image, characterized in thatwherein the AC current cycle of the light source and the sequential color cycle are operated out of phase in relation to each other.

8. (Currently Amended) The method as claimed in claim 7, wherein the illumination of the light valve device (4)-is further controlled to generate different colors in a space-multiplexed fashion.

9. (Previously Presented) The method as claimed in claim 7, wherein the period of time of the AC current cycle is longer than the period of time of the sequential color cycle.

10. (Previously Presented) The method as claimed in claim 7, wherein the period of time of the AC current cycle is shorter than the period of time of the sequential color cycle.

11. (Original) The method as claimed in claim 10, wherein the period of time of the AC current cycle is shorter than the display frame time of the sequential color cycle.

12. (Original) The method as claimed in claim 11, wherein at least one white segment is introduced in the sequential color cycle, providing an addition to the ordinary display frame time, wherein the period of time of the AC current cycle is shorter than said aggregate time period of the sequential color cycle.

13. (Original) The method as claimed in claim 7, wherein the AC-operated light source is driven with a square-wave current to constantly change the polarity of the square-wave current, to provide a constant power to the light source and to provide, each time before changing polarity, a current pulse driving the square-wave current to a predetermined strength which is larger than the current strength in between the current pulses.

14. (New) The projection system as claimed in claim 2, wherein the illumination unit is further adapted to generate different colors in a space-multiplexed fashion.

15. (New) The method as claimed in claim 8, wherein the period of time of the AC current cycle is longer than the period of time of the sequential color cycle.

16. (New) The method as claimed in claim 8, wherein the period of time of the AC current cycle is shorter than the period of time of the sequential color cycle.